

| | | | | | | | |
|--|--------------|------------------------------------|--|--------------------------|-------------|------------------------|-----------|
| Scale FULL | Dr By TSE | TEAM WHYACHI ROBOTICS | 814 E. FIRST AVE. DORCHESTER, WI. | A SIZE | C1 | OF | A REV. |
| Date 5-26-2003 | Chk By | TITLE: C1 CONTACTOR | | FOR: SPDT 24 VDC COIL | | | |
| THIS DRAWING AND ALL INFORMATION PRESENTED IS THE PROPERTY OF TEAM WHYACHI LLC AND IS STRICTLY CONFIDENTIAL. IT SHALL NOT BE COPIED, REPRODUCED OR REVEALED WITHOUT WRITTEN CONSENT. THIS DRAWING MUST BE RETURNED UPON REQUEST. | | | TOLERANCE (EXCEPT AS NOTED) .0 — .032 .00 — .015 .000 — .005 | QTY. | DESCRIPTION | TWR IDENTIFICATION NO. | |

NOTE: THE M4 TAPPED MOUNTING HOLES ON THE SIDE OF THE CONTACTOR ARE ONLY .20" DEEP.

IF A LONGER MOUNTING SCREW IS USED, IT MAY SHORT OUT ON THE COIL.

C-1 SPECIFICATIONS

SILVER ALLOY CONTACTS
SPDT TYPE
24 VDC COIL

48 VDC CONTACT CURRENT RATINGS

CONTINUOUS 80 A
3 MIN. 240 A
25 SEC. 500 A

COIL ACTUATION

COIL AMPERAGE 0.5 A
PULL IN TIME 15 ms
DROP OUT VOLTAGE 6 VDC

