

SANDING SEALER & WAX - P3960



Additional Supplies Needed: sandpaper (80, 120, 220 and 400-grit), 2 lint-free cloths

INSTRUCTIONS

- 1. Sand Car Body** Sand car with #80-grit sandpaper, followed by #120-grit. Wipe car to remove dust.
- 2. Apply Sanding Sealer** Using the Foam Brush, apply Sanding Sealer in a thin, even coat. Let dry thoroughly. (Approx. 20-30 minutes. Drying times may vary).
- 3. Sand Car Body and Re-apply Sealer** When dry, sand car with #220-grit sandpaper. Wipe car to remove dust. Apply at least 2-4 coats of Sanding Sealer (repeat Steps 2 and 3). Sand lightly on final coat. **NOTE:** Car must be thoroughly dry before painting. If car is damp, paint may bubble.
- 4. Paint Car** Once you are satisfied with car surface, paint as usual. Sand lightly with #400-grit sandpaper between coats. Apply a final light coat of paint, but do not sand. Let dry thoroughly.
- 5. Apply Wax** Apply a small amount of Wax to cloth. Wipe Wax over car surface and let set a few minutes. Wipe off car with a clean, dry cloth.



WARNING: Choking Hazard! Small parts. Not intended for children under 3 yrs. Adult supervision required.

**Conforms to Health Requirements
of ASTM D4236**

Made in USA E7 ©2009 O CO

PINECAR® Manufactured by **WOODLAND SCENICS®** PO Box 98, Linn Creek, MO 65052 • pinecar.com